LYNX pro-audio

CULTURE OF SOUND

JUNO SERIES CATALOGUE

LATEST EDITION

JUNO Series

WEATHER-RESISTANT SPEAKERS FOR INDOORS/OUTDOORS

The Juno Series are weather-resistant, two-way full range loudspeakers. The Juno series comprises one 6" low/mid-woofer with one 1" HF driver (JN-6T) and one 8" low/mid-woofer with one 1" HF driver (JN-8T), both with line transformer as standard.

High durability and superior performance with full sound over a large listening area. These cabinets have a sturdy structure and IP rated system which can be used both indoors and outdoors, being able to withstand the elements. Also, their elegant and discreet design make them the ideal speaker for outdoor installations such as beach clubs, pools, cruise ships and terraces.

Juno series can be set up either vertically or horizontally. The body is made of engineered plastic injection moulding and polypropylene guaranteeing complete protection against ultraviolet rays. The grille is perforated aluminium, internally covered in waterproof fabric and open cell expanded polyurethane.

The system conforms to IP46 international standard. JN-6T and JN8T cabinets are equipped with multitap transformer.

- Meeting rooms
- Commercial centers
- Beach clubs
- Cruise ships
- Outdoor backgroung music
- Waterparks & pools

JN-8T

Weather resistant two-way full range loudspeaker. Consists of one 8” mid-woofer with one 1” HF driver, with a multitap transformer. 122 dB SPL.

High durability and superior performance with full sound over a large listening area. These cabinets have a sturdy structure and IP rated system which can be used both indoors and outdoors, being able to withstand the elements. Black or white versions available.

Components	1×8” (200 mm) / 2” voice coil LF 1×1” (25 mm) / 1” voice coil HF
Max SPL	116 dB / 122 dB Peak
Coverage (-6dB)	90° H x 50° V
RMS Power	150 W
Transformer taps	8 Ω / 100 V: 37.5 W / 75 W / 150 W
Crossover frequencies	2.3 KHz passive
Dimensions	450 x 240 x 287 mm (H x W x D)
Weight	10 Kg (22.05 lbs)

JN-6T

Weather resistant two-way full range loudspeaker. Consists of one 6” mid-woofer with one 1” HF driver, with a multitap transformer. 116 dB SPL.

High durability and superior performance with full sound over a large listening area. These cabinets have a sturdy structure and IP rated system which can be used both indoors and outdoors. Black or white versions available.

Components	1×6” (150 mm) / 1.5” voice coil LF 1×1” (25 mm) / 1” voice coil HF
Max SPL	110 dB / 116 dB Peak
Coverage (-6dB)	90° H x 60° V
RMS Power	80 W
Transformer taps	16 Ω / 100 V: 20W / 40 W / 80 W
Crossover frequencies	2.4 KHz passive
Dimensions	362 x 182 x 232 mm (H x W x D)
Weight	6 Kg (12.23 lbs)

LYNX
pro-audio
CULTURE OF SOUND
www.lynxproaudio.com