LYNX pro-audio

CULTURE OF SOUND

KR SERIES CATALOGUE

LATEST EDITION

KR Series

PASSIVE CABINETS FOR CLUBS & KTV

The two full-range models belonging to the KR Series have been specifically designed for installations where high volume is required whilst delivering excellent vocal clarity with low distortion. They are available in two-way passive 10” and 12” versions.

Ideal for a wide range of fixed installation applications, such as KTV rooms, conference halls, houses of worship or multimedia spaces.

The double port located at the rear of the enclosure creates increased bass frequency response. When installed close to a wall, it creates a reflection that extends the low frequency response of the system, creating extra bass boost.

- KTV rooms
- Public buildings
- Houses of worship
- Conference halls
- Clubs & bars
- Sound reinforcement
- Multi media spaces

KR-12



The KR-12 is a compact, two-way passive cabinet. Consists of a 12" (3" voice coil) LF transducer with total waterproof cone treatment. The 1" HF compression driver delivers excellent sonic quality. It has an exceptional dynamic range and produces even the most complex signals with depth and definition and is mounted on a 90° x 60° rotatable horn.

Components	LF: 12" speaker, 3" (75 mm) copper wire voice coil, waterproof cone with treatment on both sides HF: 1" exit throat (38 mm) voice coil, BMS annular diaphgram driver
Max SPL	124 dB / 130 dB Peak
Coverage	90° x 60° rotatable
Rated power	500 W AES (1000 W program, 2000 W Peak)
Dimensions	600 x 363 x 410 mm (H x W x D)
Weight	24 Kg (52.9 lbs)
Fittings	14 x M8, ergonomic handle on the back position, 4 x M6 U-bracket, 4 x M6 wall bracket, 35 mm top hat

KR-10



The KR-10 is a compact, two-way passive cabinet. Consists of a 10" (2.5" voice coil) LF transducer with waterproof cone. The 1" HF compression driver delivers excellent sonic quality. It has an exceptional dynamic range and produces even the most complex signals with depth and definition and is mounted on a 90° x 60° rotatable horn.

Components	LF: 10" speaker, 2.5" (50 mm) fiber glass former and aluminium winding voice coil, waterproof cone with treatment on both sides HF: 1" exit throat (38 mm) voice coil, BMS annular diaphgram driver
Max SPL	122 dB / 128 dB Peak
Coverage	90° x 60° rotatable
Rated power	300 W AES (600 W program, 1200 W Peak)
Dimensions	550 x 295 x 330 mm (H x W x D)
Weight	16 Kg (35.2 lbs)
Fittings	14 x M8, ergonomic handle on the back position, 4 x M6 U-bracket, 6 x M6 wall bracket, 35 mm top hat

ACCESSORIES KR SERIES

KR-10	**AGR-8** Eye bolt 	**WB-20/3** Wall bracket 	**UBR-KR10** U bracket 
KR-12	**AGR-8** Eye bolt 	**WB-20/3** Wall bracket 	**UBR-KR12** U bracket 

LYNX
pro-audio
CULTURE OF SOUND
www.lynxproaudio.com