LYNX pro-audio

CULTURE OF SOUND

ROX SERIES CATALOGUE

LATEST EDITION

ROX Series

PORTABLE CABINETS

The ROX Series is our answer to multi-purpose, full-range cabinets at affordable pricing.

The series comprises four self-powered, full-range cabinets with integrated FIR Filter DSP, BT connectivity, and a two-channel mixer, now complemented by two powerful active subwoofers for professional low-frequency reinforcement..

Built with durability and portability in mind, the ROX Series is easy to transport, set up, and optimize for live performances, DJ sets, or corporate events. Its lightweight design, combined with a rugged build, makes it the go-to choice for professional sound technicians and event planners seeking reliable, high-quality sound.

- Installations in nightclubs & bars
- Large and medium-sized stadiums
- Live events

RX-8

The RX- 8 is a high-performance polypropylene, 2-way active PA system featuring a 8-inch low-frequency driver. Powered by a Class D amplifier, it delivers 280 W RMS and can reach a peak output of 600 W.

Components	LF: 8", 2" voice coil HF: 1", compression driver
Amplification	Class-D/ DSP FIR Filters
Power	280W RMS / 600W Peak
Frequency Response	65 Hz to 20 kHz
SPL Max	118 dB - 124 dB Peak
Coverage	90°H x 60°V
Inputs	2 balanced Combo Jack/XLR inputs with MIC/LINE selector and adjustment level for each input.1 3.5mm mini-jack AUX input
Outputs	Balanced XLR LINE-level output
Control	LCD Display, encoder and push button
BT	Receiver-TWS Stereo Pairing
Power Supply	230V ~ / 50Hz mains power supply
Dimensions	435 x 245 x 295 mm (H x W x D)
Weight	12 Kg (20.46 lbs)

RX-10

The RX- 10 is a high-performance polypropylene, 2-way active PA system featuring a 10-inch low-frequency driver. Powered by a Class D amplifier, it delivers 280 W RMS and can reach a peak output of 600 W.

Components	LF: 10", 2" voice coil HF: 1", compression driver
Amplification	Class-D/ DSP FIR Filters
Power	280 W RMS / 600 W Peak
Frequency Response	45 Hz to 20 kHz
SPL Max	119 dB - 125 dB Peak
Coverage	90° H x 60° V
Inputs	2 balanced Combo Jack/XLR inputs with MIC/LINE selector and adjustment level for each input.1 3.5mm mini-jack AUX input
Outputs	Balanced XLR LINE-level output
Control	LCD Display, encoder and push button
BT	Receiver-TWS Stereo Pairing
Power Supply	230V ~ / 50Hz mains power supply
Dimensions	545 x 355 x 295 mm (H x W x D)
Weight	15 Kg (33.07 lbs)

RX-12

The ROX-12 is a high-performance polypropylene, 2-way active PA system featuring a 12-inch low-frequency driver. Powered by a Class D amplifier, it delivers 450 W RMS and can reach a peak output of 1000 W.

Components	LF: 12", 3" voice coil HF: 1.35", compression driver
Amplification	Class-D
Power	450W RMS / 1000 W Peak
Frequency Response	45Hz to 20 kHz
SPL Max	125 dB - 131 dB Peak
Coverage	90° H x 60° V
Inputs	2 balanced Combo Jack/XLR inputs with MIC/LINE selector and adjustment level for each input.1 3.5mm mini-jack AUX input
Outputs	Balanced XLR LINE-level output
Control	LCD Display, encoder and push button
BT	Receiver-TWS Stereo Pairing
Power Supply	230V ~ / 50Hz mains power supply
Dimensions	609 x 359 x 346 mm (H x W x D)
Weight	21 Kg (46.30 lbs)

RX-15

The ROX-15 is a high-performance polypropylene, 2-way active PA system featuring a 15-inch low-frequency driver. Powered by a Class D amplifier, it delivers 450 W RMS and can reach a peak output of 1000 W.

Components	LF: 15", 3" voice coil HF: 1.35", compression driver
Amplification	Class-D
Power	450 W RMS / 1000 W Peak
Frequency Response	45 Hz to 20 kHz
SPL Max	125 dB 131 dB Peak
Coverage	90° H x 60° V
Inputs	2 balanced Combo Jack/XLR inputs with MIC/LINE selector and adjustment level for each input.1 3.5mm mini-jack AUX input
Outputs	Balanced XLR LINE-level output
Control	LCD Display, encoder and push button
BT	Receiver-TWS Stereo Pairing
Power Supply	230V ~ / 50Hz mains power supply
Dimensions	696 x 417 x 368 mm (H x W x D)
Weight	23 Kg (50.71 lbs)

RX-S15

The RX-S15 is a high-output, self-powered subwoofer enclosure specially designed to reinforce the low frequencies of the full-range models of the ROX series. Compact and versatile, this unit features a 1200 W Class-D amplifier with a switching power supply. It consists of a 15" (4" voice coil) transducer, delivering a maximum of 132 dB SPL peak.

Components	1 x 15", 4" voice coil
Max SPL	126 dB - 132 dB Peak
Coverage	Omnidirectional
Frequency Response	45 Hz - 250 Hz (- 3dB) Adjustable
Power	1200W Class D with switching power supply
Processing	Analogue
Control	User control interface
Dimensions	500 x 450 x 572 mm (H x W x D)
Weight	33 Kg (72.75 lbs)

RX-S18

The RX-S18 is a high-output, self-powered subwoofer enclosure specially designed to reinforce the low frequencies of the full-range models of the ROX series. It features a 1200 W Class-D amplifier with a switching power supply, offering high performance in a compact format. It consists of an 18" (4" voice coil) transducer, achieving an impressive 134 dB SPL peak.

Components	LF: 1 x 18", 4" voice coil
Max SPL	128 dB - 134 dB Peak
Coverage	Omnidirectional
Frequency Response	35 Hz - 250 Hz (- 3dB) Adjustable
Power	1200W Class D with switching power supply
Processing	Analogue
Control	User control interface
Dimensions	542 x 560 x 780 mm (H x W x D)
Weight	42 Kg (92.59 lbs)

LYNX
pro-audio
CULTURE OF SOUND
www.lynxproaudio.com