GXR-D18P

GXR SERIES DATASHEET

High output bass reflex, omni-directional subwoofer cabinet. Consists of 2 x 18” (4” voice coil).



Key features

- Passive

Applications

- Live events
- Houses of worship
- Fixed installations
- Clubs
- Theatres
- Touring

Technical Data

Components	
• LF:	2 x 18”, 4” voice coil
Frequency range	30 Hz - 120 Hz (-10dB) processed
Frequency response	35 Hz - 100 Hz (± 3dB) processed
Sensitivity	100 dB
Max SPL / Peak	LF: 134 dB / 139 dB
Crossover	Electronic crossover
Coverage	Omnidirectional
Rated Power	3200W AES, 6400W program, 12800W peak
Nominal impedance	2 x 8 Ω total 4 Ω
Connectors	2 x neutrik NL4
Finish	Polyurea coating, high grade resistant paint
Material	18 mm Premium birch plywood
Dimensions	605 x 1100 x 750 mm (H x W x D)
Weight	90 Kg (198.4 lbs)

Dimensions



Accessories



CA-GXRLD15
Transport dolly for GXR-D18A

FD-GXRLA10
Nylon protection cover for either 4 GXR-LA210A cabinets



GX-18WKIT
Wheel kit for subwoofer GXR-D15A and GXR-D18A