

High Output, compact bi-amp line array module. Consists of 2 x 10" (2" voice coil) transducer with 1.4" exit throat driver.



### Key features

- Passive bi-amplified
- Two way active system

### Applications

- Live events
- Houses of worship
- Fixed installations
- Clubs
- Theatres
- Touring

### Technical Data

<b>Components</b>	
• LF:	LF: 10", 2" voice coil, Malt Cross Cooling System
• HF:	HF: 1.4"exit throat, 3" voice coil with titanium diaphragm
<b>Frequency range</b>	60 Hz - 20 KHz (-10 dB) PROCESSED
<b>Frequency response</b>	65 Hz - 18 KHz (± 3dB) PROCESSED
<b>Sensitivity</b>	LF: 99dB HF: 109 dB
<b>Max SPL</b>	LF: 127 dB/ 133dB HF: 128 dB / 134 dB
<b>Crossover</b>	ELECTRONIC FIR FILTERS LINEAR PHASE
<b>Coverage</b>	H: 100°V: depending number cabinets of array
<b>Rated Power</b>	LF: 600W AES, 1200W program, 2400W peak HF: 80W AES, 160 W program, 320 W peak
<b>Nominal impedance</b>	LOW 8 ohms HIGH 16 ohms
<b>Connectors</b>	2 x neutrik NL4
<b>Finish</b>	Polyurea coating, high grade resistant paint
<b>Material</b>	15 mm Premium birch plywood
<b>Dimensions</b>	299 x 790 x 436 mm (H x W x D)
<b>Weight</b>	29 Kg (63.9 lbs)

### Dimensional Drawing

