

High power, ultra compact, subwoofer cabinet with two 15" low frequency transducers with rubber suspension in triple band-pass configuration. 139dB Peak (4000W program).



### Key features

- Ultra compact triple band-pass
- Versatile sound reinforcement
- High performance 1200 W
- ARK processor optimised preset

### Applications

- Club & bar installations
- Sound reinforcement
- Theatres
- Houses of worship
- Multi media spaces
- Public address

### General description & specifications

The HR-215S is a high-performance compact subwoofer designed to work with the HR range full range cabinets, offering impressive low-frequency reinforcement with an excellent power-volume-to-weight ratio.

High power, ultra compact, sub-bass cabinet with two 15" low frequency transducers with rubber suspension in triple band-pass configuration. 139dB Peak (4000W program).

### Technical Data

<b>Components</b>	
• LF	2 x 15" transducers
<b>Frequency range</b>	30 Hz – 160 Hz (-10dB)
<b>Frequency response</b>	35 Hz – 150 Hz (± 3dB)
<b>Sensitivity</b>	100 dB (1W@1m) π
<b>Max SPL</b>	133 dB – 139 dB Peak
<b>Coverage Angle</b>	Quasi omnidirectional
<b>Power</b>	2000 W (4000 W program, 8000 W peak)
<b>Crossover</b>	Active
<b>Nominal impedance</b>	4 Ω
<b>Connectors</b>	2 x Neutrik Speakon NL4MP
<b>Finish</b>	Polyurea coating - other colours (RAL) available
<b>Material</b>	18 mm premium birch plywood
<b>Dimensions</b>	644 x 463 x 600 mm (H x W x D)
<b>Weight</b>	59 Kg (130 lbs)

## Dimensional Drawing

