

SB-215

ULTRA-COMPACT
TRIPLE BAND-PASS
SUB WOOFER



DATA SHEET

pag.1/2 V.12.01

- ▶ Ultra-Compact
- ▶ Very High Performance 4000w
- ▶ Versatile Sound reinforcement
- ▶ ARK optimised preset
- ▶ White & black colour optional



APPLICATIONS

- Club and Bar Installs
- House of Worship
- Live Sound
- Theatres
- Broadcast
- Multi media spaces

GENERAL DESCRIPTION

The power to size ratio achieved from this cabinet is quite spectacular. The SB-215 is an extremely compact, very high power, passive sub-bass cabinet in triple band pass configuration delivering 2000W RMS.

It features dual 15" transducers (4" voice coil) with rubber surround for increased levels of pressure, double spider for improved control and linearity, weather protected cone for outdoor use and ventilated voice coil for improved heat dissipation. The SB-215 has been designed to be used with the QB-12, QB-15, QB-D6 and QB-D8 to extend the low frequency support.

It is made from premium birch plywood and coated with high resistant water-based black paint, includes integrated handles, rubber feet and top hat insertion point for satellite combination with the QB Series.

SPECIFICATIONS

COMPONENTS	LF 2 x 15" transducer 100 mm voice coil
FREQUENCY RANGE	30 Hz - 160 Hz
FREQUENCY RESPONSE	35 Hz - 150 Hz
SENSIVITY 1w @ 1m	103 dB
MAX SPL 1w@ 1m	138 dB
RATED POWER RMS	2000 W
PROGRAM POWER	4000 W
COVERAGE	360° single unit
NOMINAL IMPEDANCE	4 Ohms
CONNECTORS	2 x Neutrik Speakon NL4MP
CONSTRUCTION	18 mm Premium Birch plywood
FINISH	High resistant water-based black paint Black
FITTINGS	1 x Top hat 4 x rubber feet 2 x integrated handles
DIMENSIONS (H x W x D)	644 x 463 x 600 mm
WEIGHT	59 Kg

SB-215

ULTRA-COMPACT
TRIPLE BAND-PASS
SUB WOOFER



DATA SHEET

pag.2/2 V.12.01

PREDICTION SOFTWARE:



- RAINBOW

Acoustical Prediction software for accurate loudspeaker planning offering both horizontal and vertical views.

ARK optimised preset

SB-215.equ

Compatible with all ARK and DAC versions

ACCESSORIES



TU-C01



TU-C02



VAS-01



VAS-02

DIMENSIONS

