

# SUB-08

ULTRA COMPACT  
DOUBLE BAND PASS  
SUB WOOFER



DATA SHEET

pag.1/2 V.06.17

- ▶ Ultra- compact Light weight
- ▶ Background sound reinforcement
- ▶ ARK optimised preset
- ▶ White & black colour optional
- ▶ High quality component



## APPLICATIONS

- Club and Bar Installs
- House of Worship
- Theatres
- Broadcast
- Multi media spaces

## GENERAL DESCRIPTION

The SUB-08 is an ultra compact double band pass sub woofer delivering high-performance for background sound applications.

It uses one 8" transducer with rubber surround and double independent coil. The SUB-08 has been designed to be used with the QB-5 to extend the low frequency support.

It is made from premium birch plywood and coated with high resistant water-based black paint.

## SPECIFICATIONS

COMPONENTS	LF 1 x 8" transducer 2 x 50 mm voice coil
FREQUENCY RANGE	43 Hz - 160 Hz
FREQUENCY RESPONSE	47 Hz - 154 Hz $\pm 3$ dB
SENSIVITY 1w @ 1m	93 dB
MAX SPL	116 dB - 122 dB peak
RATED POWER RMS	2 x 100 W
PROGRAM POWER	2 x 200 W
COVERAGE	360° single unit
NOMINAL IMPEDANCE	2 x 8 Ohms
CONNECTORS	2 x Neutrik Speakon NL4MP
CONSTRUCTION	15 mm Premium Birch plywood
FINISH	High resistant water-based black paint Black
FITTINGS	4 x rubber feet
DIMENSIONS (H x W x D)	268 x 641 x 304 mm
WEIGHT	9 Kg

## ARK optimised preset

SUB-08.equ

Compatible with all ARK versions

## PREDICTION SOFTWARE:



- RAINBOW

Acoustical Prediction software for accurate loudspeaker planning offering both horizontal and vertical views.

## DIMENSIONS

